



SABA Primer 4518

primer for polypropylene

Description

SABA Primer 4518 is a 1-component primer for pre-treating polypropylene.

Field of application

The marine, transport, building and industry sectors. SABA Primer 4518 is very suitable for pre-treating surfaces of polypropylene surfaces, such as MonoPan® and Twintex®.

Advantages

- excellent adhesion to polypropylene

Method of use

Always clean the surfaces with Sabaclean 48 in advance.

For instructions for use, see the relevant info sheets on www.saba.nl

Seal the container as soon as possible after use: this has a positive effect on the processing properties and the shelf life of the product.

Technical data

Basis	chlorine rubber
Viscosity at 23 °C (EN 12092)	approx. 10 mPa.s
Density (EN ISO 2811-2)	approx. 870 kg/m ³
Solids content	approx. 2,5 %
Flashpoint	approx. 25 °C
Solvents	mixture of aromatics
Open time	15 to 30 minutes
Coverage	ca. 100 g/m ²
Working temperature	min. + 5 °C to max. + 30 °C
Storage temperature	min. + 5 °C to max. + 30 °C
Temperature resistance	min. - 40 °C to max. + 90 °C

Order information

Packaging	bottle with resealable cap
Contents	250 ml (contains 24 items)
Colour	transparent
Article no.	100347 AAQ
Shelf life	24 months (in unopened packing)

Other packaging on request. The shelf life may vary for large packaging.

Safety recommendations

For more information about safety, see the relevant SABA safety data sheet.