



Product Data Sheet

Sabafinish

smoothing agent

Description

Sabafinish is a smoothing agent for providing a smooth, modelled finish for sealed seams. Sabafinish is designed to be extremely neutral, so that a white sealed seam stays white.

Field of application

Smoothing agent for providing a smooth, modelled finish for sealed seams with Sabatack or Sabaflex sealants and adhesives.

Benefits

- neutral
- does not affect coatings and plastics
- does not affect the joints: a white sealed seam stays white

Method of use

For application please read the corresponding info sheets on www.saba.nl

Technical data

Basis	surfactant
Viscosity at 23 °C (EN 12092)	water like
Density (EN ISO 2811-2)	approx. 1000 gr. / litre
Work temperature	minimum + 5 °C to maximum + 35 °C
Storage temperature	minimum + 5 °C to maximum + 30 °C

Order information

Packing	can with reclosable cover
Content	5 litre
Colour	transparant
Article no.	100367 ACB
Shelf life	12 months (in unopened packing)

Other packing and colours on request. On large packing the shelf life can be different.

Safety recommendations

For more information concerning safety please read the corresponding SABA safety data sheet.

SABA Dinxperlo BV

Industriestraat 3 NL-7091 DC Dinxperlo PO Box 3 NL-7090 AA Dinxperlo T +31 (0)315 65 89 99 F +31 (0)315 65 89 89 E info@saba.nl www.saba.nl

Our recommendations and instructions for use are based on the present status of know-how and technique. Clients and users should evaluate our products by themselves, with regard to utilization and requirements of their own choice. We shall take no responsibility in case our products are not being used subject to our recommendations and/or instructions for use. Furthermore, General Terms and Conditions of SABA Dinxperlo BV will apply to our recommendations, instructions for use and the delivery of our products.