

TICOL[®] TEAK CLEANER

TC-201

TEAK CLEANER

Product Identification

TICOL[®] Teak Cleaner is formulated for the maintenance of hardwoods like teak, irecco and etc. It is used to clean the oil and other dirt on the surfaces and furthermore, partly refresh the color of the substrate. Depending on the level of cleaning after this cleaner, TICOL[®] Teak Brightener is advised for deeper (pore) cleaning and better color refreshment. It can be used on decking (boat, pool), building elements, flooring and outdoor furniture made up of hardwood.

Application Recommendations

Ready-to use, no need for further thinning. Stir well before use. Application by brush, sponge or cloth is advised. In order to achieve deep cleaning in the pores, brushing will be necessary. Rinse the surface well after use.

Application Amount

Application amount can differ according to the type of the wood, condition of the surfaces, level of aging after previous maintenance. 10 – 12 sq. meters of area can be treated with 1 Liter of material.

Drying Time

Technical Properties

Non-volatiles, weight, %	5 ± 2
Density, gr/cm ³ @20°C	1,02 ± 3

TICOL[®] TEAK CLEANER

Notes

Prior to the application, the surfaces should be free from dust. For deeper claning and wood refreshment, Ticol[®] Teak Brightener is suggested.

Safety and Storage

Taking necessary precautions stated in the safety data sheet (MSDS) and assuring good ventilation during application is the responsibility of the user. Follow the information on the labels and the MSDS.

In the original, closed cans, under cool and dry stocking conditions (above 5 °C) , expiry date is three years after the production.

Packing

0,50 L (PET), 1,0 L (PET), 5 L (PE), and 20 L (PE)

This data sheet, revises any other data sheet issued older than this one. Data enclosed, specifications and recommendations are made according to either international test standards or under specified / controlled, experienced application conditions. It is recommended to test the validity and conformity of those in beforehand. The manufacturer can make revisions on the product without any notice. Unless revised, this Technical Data Sheet is valid for 5 years.